LISTING OF CLAIMS:

Claim 1-25 (Previously canceled).

Claim 26 (Currently amended): A tool assembly comprising:

an anvil and a cartridge assembly, the cartridge assembly having a plurality of fasteners and being movable in relation to the anvil between a spaced position and an approximated position, the cartridge assembly and anvil defining a tissue gap in the approximated position;

a clamp member positioned adjacent a proximal end of the cartridge assembly and the anvil and being movable from a first position to a second position, the clamp member being configured to maintain the proximal end of the cartridge assembly and the anvil in juxtaposed alignment when the clamp member is in the second position; and

a dynamic clamping member movably positioned in relation to the anvil and the cartridge assembly, the dynamic clamping member being movable from a first position to a second position and configured to define a maximum tissue gap between the cartridge assembly and the anvil adjacent the dynamic clamping member during ejection of the plurality of fasteners from the cartridge assembly; and[[.]]

a drive member operably connected to the clamp member and the dynamic clamping

member, the drive member being formed from a cable and being movable to move the clamp

member and the dynamic clamping member between their first and second positions, wherein the

drive member includes a coaxial drive cable, the coaxial drive cable including an outer sheath

Appl. No. 10/529,800

Amdt. Dated September 29, 2008

Reply to Office Action of May 28, 2008

and a center rod.

Claim 27 (canceled)

Claim 28 (canceled)

Claim 29 (Currently amended): A tool assembly according to Claim [[28]] 26, wherein

the center rod is movable in relation to the outer sheath.

Claim 30 (Previously presented): A tool assembly according to Claim 29, wherein the

center rod is axially movable with respect to the outer sheath.

Claim 31 (Previously presented): A tool assembly according to Claim 29, wherein the

center rod is rotatable in relation to the outer sheath.

Claim 32 (Currently amended): A tool assembly according to Claim [[28]] 26, wherein

the outer sheath is operably connected to the clamp member.

Claim 33 (Previously presented): A tool assembly according to Claim 32, wherein the

center rod is operably connected to the dynamic clamping member.

Claim 34 (Previously presented): A tool assembly according to Claim 26, wherein the

tool assembly is pivotally secured to a body portion of a stapling device.

Claim 35 (Previously presented): A tool assembly according to Claim 34, wherein the

tool assembly is operably connected to a collar member and the collar member is pivotally

secured to the body portion of the stapling device.

Claim 36 (Previously presented): A tool assembly according to Claim 35, wherein the

tool assembly is rotatably mounted to the collar member.

Claim 37 (Previously amended): A tool assembly according to Claim 36, wherein a

Amdt. Dated September 29, 2008

Reply to Office Action of May 28, 2008

center rod of a coaxial cable is operably connected to the dynamic clamping member and the

dynamic clamping member is supported in the tool assembly such that rotation of the center rod

effects rotation of the dynamic clamping member which effects rotation of the tool assembly.

Claim 38 (Previously presented): A tool assembly according to Claim 26, wherein the

dynamic clamping member includes a first flange portion positioned to engage a surface of the

anvil and a second flange portion positioned to engage a surface of the cartridge assembly, the

first and second flange portions being positioned to define a maximum tissue gap adjacent the

dynamic clamping member during movement of the dynamic clamping member from its first to

its second position.

Claim 39 (Previously presented): A tool assembly according to Claim 38, wherein the

clamp member is annular and is positioned about a proximal end of the anvil and of the cartridge

assembly in its second position to define a maximum tissue gap at a proximal end of the tool

assembly.

Claim 40 (Currently amended): A tool assembly according to Claim [[28]] 26, wherein

the center rod is formed from wound flexible cable.

Claim 41 (Currently amended): A tool assembly according to Claim [[28]] 26, wherein

the outer sheath is selected from the group consisting of steel mesh, plastic, nitinol, and Kevlar.

Claim 42 (Previously presented): A tool assembly according to Claim 26, further

including a knife blade associated with the dynamic clamping member.

Claim 43 (Previously presented): A tool assembly according to Claim 42, wherein the

knife blade is formed on the dynamic clamping member.

Appl. No. 10/529,800

Amdt. Dated September 29, 2008

Reply to Office Action of May 28, 2008

Claim 44 (Currently Amended): A tool assembly according to Claim [[28]] 26 wherein

the tool assembly includes a drive collar and the outer sheath is fixedly attached to the drive

collar.

Claim 45 (Previously presented): A tool assembly according to Claim 26, wherein the

first position of the dynamic clamping member is adjacent a proximal end of the tool assembly

and the second position of the dynamic clamping member is adjacent a distal end of the tool

assembly.

Claim 46 (Previously presented): A tool assembly according to Claim 26, wherein the

cartridge assembly includes a sled and at least one pusher associated with each of the plurality of

fasteners, the sled being driven by the dynamic clamping member into engagement with each

pusher to advance each pusher and eject the staple from the cartridge assembly.

Claim 47 (Previously presented): A tool assembly according to Claim 46, wherein the

cartridge assembly includes a plurality of staples and pushers.

Claim 48 (Currently amended): A tool assembly for use with a surgical stapler

comprising:

an anvil;

a cartridge assembly having at least one staple, the cartridge assembly being movable in

relation to the anvil between spaced and approximated positions;

a clamp member positioned adjacent a proximal end of the tool assembly, the clamp

member being movable from a retracted position to an advanced position and being configured

to maintain a proximal end of the anvil and cartridge assembly in the approximated position

Appl. No. 10/529,800

assembly.

Amdt. Dated September 29, 2008

Reply to Office Action of May 28, 2008

when the clamp member is in the advanced position; and

a dynamic clamping member positioned within the tool assembly and movable from a retracted position through the tool assembly to an advanced position to eject staples from the cartridge assembly, the dynamic clamping member including an upper flange portion engaging a surface of the anvil and a lower flange portion engaging a surface of the cartridge assembly, at least one of the upper and lower flange portions having a-rounded an arcuate cross-section along an axis transverse to a longitudinal axis of the cartridge assembly to define an arcuate surface positioned to engage at least one of the surface of the anvil and the surface of the cartridge assembly, the dynamic clamping member being configured to define a maximum tissue gap between the anvil and the cartridge assembly during ejection of staples from the cartridge

Claim 49 (Previously presented): A tool assembly according to Claim 48, further including a knife blade associated with the dynamic clamping member.

Claim 50 (Previously presented): A tool assembly according to Claim 49, wherein the knife blade is formed on a central body portion of the dynamic clamping member.

Claim 51 (Previously presented): A tool assembly according to Claim 50, wherein the cartridge assembly includes a sled and at least one pusher associated with each of the at least one staple, the sled being driven by the dynamic clamping member into engagement with each pusher to advance each pusher and eject the staple from the cartridge assembly.

Claim 52 (Previously presented): A tool assembly according to Claim 51, wherein the cartridge assembly includes a plurality of staples and pushers.

Appl. No. 10/529,800 Amdt. Dated September 29, 2008

Reply to Office Action of May 28, 2008

Claim 53 (Previously presented): A tool assembly according to Claim 52, wherein the

upper flange and lower flange are substantially vertically aligned.

Claim 54 (Previously presented): A tool assembly according to Claim 53, wherein the

knife blade is disposed on the central body portion between the upper and lower flanges.